





## N-Channel Enhancement Mode Field Effect Transistor




Top View



Bottom View

SOT-23



### Product Summary

- $V_{DS}$  60V
- $I_D$  2.3A
- $R_{DS(ON)}$  (at  $V_{GS}=10V$ )  $<94m\Omega$
- $R_{DS(ON)}$  (at  $V_{GS}=4.5V$ )  $<126m\Omega$
- ESD protected up to 1.0KV (HBM)

### General Description

- Low  $R_{DS(on)}$  & FOM
- Extremely low switching loss
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Part no. with suffix "Q" means AEC-Q101 qualified
- Halogen Free

### Applications

- Relay driver
- High-speed line driver
- Low-side load switch
- Switching circuits

### ■ Limiting Values

Parameter	Conditions		Symbol	Min	Max	Unit	
Drain-source Voltage			$V_{DS}$	-	60	V	
Gate-source Voltage			$V_{GS}$	-20	20		
Continuous Drain Current (Note 1,2)	Steady-State	$T_A=25^\circ C, V_{GS}=10V$		$I_D$	-	2.3	
		$T_A=100^\circ C, V_{GS}=10V$			-	1.5	
Pulsed Drain Current	$T_A=25^\circ C, t_p \leq 10\mu s$		$I_{DM}$	-	18.4	A	
Maximum Body-Diode Continuous Current	$T_A=25^\circ C$		$I_S$	-	2.3		
Total Power Dissipation (Note 1,2)	Steady-State	$T_A=25^\circ C$		$P_D$	-	1.1	W
		$T_A=100^\circ C$			-	0.4	
Junction and Storage Temperature Range			$T_J, T_{STG}$	-55	150	°C	

### ■ Thermal Resistance

Parameter	Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient (Note 2)	$R_{QJA}$		116	°C/W

### ■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJL094N06AJKQ	F2	094N06	3000	30000	120000	7" reel



## ■ Electrical Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Units
<b>Static Parameter</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	$V_{GS}=0V, I_D=250\mu A, T_j=25^\circ C$	60	-	-	V
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS}=60V, V_{GS}=0V, T_j=25^\circ C$	-	-	1	$\mu A$
		$V_{DS}=60V, V_{GS}=0V, T_j=150^\circ C$	-	-	100	$\mu A$
Gate-Source Leakage Current	$I_{GSS}$	$V_{GS}=\pm 20V, V_{DS}=0V, T_j=25^\circ C$	-	-	$\pm 10$	$\mu A$
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A, T_j=25^\circ C$	1.1	1.6	2.1	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=2A, T_j=25^\circ C$	-	74	94	$m\Omega$
		$V_{GS}=4.5V, I_D=1A, T_j=25^\circ C$	-	84	126	$m\Omega$
Diode Forward Voltage	$V_{SD}$	$I_S=2A, V_{GS}=0V, T_j=25^\circ C$	-	0.82	1.2	V
Gate Resistance	$R_G$	$f=1MHz, T_j=25^\circ C$	-	6	-	$\Omega$
<b>Dynamic Parameters</b>						
Input Capacitance	$C_{iss}$	$V_{DS}=30V, V_{GS}=0V, f=1MHz, T_j=25^\circ C$	-	316	-	pF
Output Capacitance	$C_{oss}$		-	21	-	
Reverse Transfer Capacitance	$C_{rss}$		-	16	-	
<b>Switching Parameters</b>						
Total Gate Charge	$Q_g$	$V_{GS}=10V, V_{DS}=30V, I_D=2A, T_j=25^\circ C$	-	6.6	-	nC
Gate-Source Charge	$Q_{gs}$		-	1.1	-	
Gate-Drain Charge	$Q_{gd}$		-	1.4	-	
Reverse Recovery Charge	$Q_{rr}$	$I_F=2A, di/dt=100A/\mu s, V_{GS}=0V, V_R=30V, T_j=25^\circ C$	-	8	-	nC
Reverse Recovery Time	$t_{rr}$		-	12.8	-	ns
Turn-on Delay Time	$t_{D(on)}$	$V_{GS}=10V, V_{DS}=30V, I_D=2A, R_{GEN}=3\Omega, T_j=25^\circ C$	-	4.6	-	ns
Turn-on Rise Time	$t_r$		-	2.6	-	
Turn-off Delay Time	$t_{D(off)}$		-	14.3	-	
Turn-off Fall Time	$t_f$		-	2.7	-	

Note:

- The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
- The value of  $R_{\theta JA}$  is measured with the device mounted on the 40mm\*40mm\*1.1mm single layer FR-4 PCB board with 1 in<sup>2</sup> pad of 2oz. Copper, in the still air environment with  $T_A=25^\circ C$ . The maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.

## ■ Typical Electrical and Thermal Characteristics Diagrams




Figure 1. Output Characteristics; typical values




Figure 2. Transfer Characteristics; typical values




Figure 3. Capacitance Characteristics; typical values




Figure 4. Gate Charge; typical values




Figure 5. On-Resistance vs. Gate to Source Voltage; typical values




Figure 6. Normalized On-Resistance




Figure 7. RDS(on) vs. Drain Current; typical values




Figure 8. Forward characteristics of reverse diode; typical values




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area



## ■ SOT-23 Package Information




SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
MIN.	MAX.	MIN.	MAX.	
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
$\theta$	0°	8°	0°	8°

## NOTE:

- 1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
- 2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.
- 3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.



■ **Marking Information**



**Note:**

1. All marking is at middle of the product body
2. All marking is in laser printing
3. 094N06 is marking code
4. Body color: Black



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.